LLumar® iLLusions™ Decorative Window Film Specialty Series

### Red





To view this product and the rest of the LLumar<sup>®</sup> iLLusions<sup>™</sup> line, please visit **LLumar.com/decofilmviewer** 

## Specifications

Product Name	Red
Product Series	Specialty Series
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Width	60"
Film Thickness (excludes liner)	.001"

% Diffuse Performance Visible Light % Visible Light Reflectance Privacy Film Data Transmittance Rating (exterior) Clear Glass 90 8 0 1/8" (3mm) single pane /8" (3mm) single pane

\*This reflectance value is a standard specular reflectance value For the most current data please go to LLumar.com/nar-deco-specs

### **Product Description**

LLumar specialty films can mask light, add privacy or give a pop of color to any space. Bold, graphic hues and distinctive designs enliven retail spaces and commercial properties. Unique combinations of specialty films allow for endless customizable possibilities.

#### Benefits and selection criteria

- From informal to formal spaces, this hue offers a lasting impression
- Ideal to showcase corporate identity or one-of-a-kind window glass wall art
- Proprietary scratch resistant (SR) coating enhances durability and allows for easy maintenance.
- Can be custom cut to add a unique graphic element
- Helps shield harmful ultraviolet rays

### Installation and Warranty

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

# Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

#### Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.

EASTMAN LLumar.com
© 2014 Eastman Chemical Company. LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries.
As used herein, ® denotes registered trademark status in the U.S. only. Printed in U.S.A. (11/14)

